

Mitutoyo

Mitutoyo Quality

Non-stop CNC Vision Measuring System
with Tracking Auto Focus (TAF)

Quick Vision QV STREAM PLUS

Captures and tracks without stopping for astounding throughput

VISION MEASURING SYSTEMS



Non-stop CNC Vision Measuring System with Tracking Auto Focus (TAF) Quick Vision QV STREAM PLUS



FEATURES

- Enables high-throughput measurement—more than five times higher than earlier models. *Using Mitutoyo sample workpieces
- New method captures the image continuously without stopping the stage.
- Includes a tracking auto focus (TAF) feature that tracks the contours of waves and warpage on the surface of the workpiece and maintains focus. This eliminates time wasted during autofocusing.

SPECIFICATIONS

Specifications for QV STREAM PLUS Series systems with TAF

Order No.	363-176	363-186	363-196
Model	QV-X302T1S-D	QV-X404T1S-D	QV-X606T1S-D
Main unit			
Measuring range (XxYxZ)	300x200x200mm	400x400x250mm	600x650x250mm
Performance			
Accuracy E1	X, Y axes (image)	(1.5+3L/1000) μm *1	
	Z axis (image)	(1.5+4L/1000) μm *1	
Accuracy E2	XY plane (image)	(2+4L/1000) μm *1	
Resolution		0.1μm	
TAF Z-axis resolution		0.3μm	
Operating temperature range		20±1°C	
Main equipment and features			
Imaging Device		B&W CCD	
Illumination Unit	Co-axial Light	Color LED	
	Transmitted Light	Blue LED	
	PRL	Color LED (quadrant)	
Observation unit		PPT 1X-2X-6X	

*1 Determined using Mitutoyo inspection methods. Optical magnification for which accuracy guaranteed: 2.5X objective (QV-HR2.5X or QV-SL2.5) + 2X tube lens

Tracking Auto Focus (TAF)

The TAF feature focuses continuously, adjusting to changes in the height of the object being measured. Automatic tracking of surface waves and warpage (in the Z axis height direction) improves measurement throughput. The feature also cuts out the hassle of focusing during manual measurement, reducing the work burden for measuring system operators.


Note: Continuous measurement of displacement is not performed.

Tracking Auto Focus (TAF)

AF principle	Objective coaxial autofocusing (knife edge method)				
Suitable objectives	QV-HR1x	QV-SL1x	QV-HR2.5x	QV-SL2.5x	QV-5x
Tracking range*2	6.3mm (±3.15mm)	6.3mm (±3.15mm)	1mm (±0.5 mm)	1mm (±0.5 mm)	0.25mm (±0.125mm)
Spot diameter*3	5.2μm	8.0μm	2.1μm	3.1μm	1.5μm
Laser source	Semiconductor laser (peak wavelength: 690nm)				
Laser power	0.9mW				
Laser safety	Class 2 (JIS C6802:2011, EN/IEC 60825-1:2007)				

*2 Varies according to workpiece surface texture and reflectance.

*3 These are design values.



Note: Product illustrations are without obligation. Product descriptions, in particular any and all technical specifications, are only binding when explicitly agreed upon.

MITUTOYO and MiCAT are either registered trademarks or trademarks of Mitutoyo Corp. in Japan and/or other countries/regions.

Other product, company and brand names mentioned herein are for identification purposes only and may be the trademarks of their respective holders.

Our products are classified as regulated items under Japanese Foreign Exchange and Foreign Trade Law. Please consult us in advance if you wish to export our products to any other country. If the purchased product is exported, even though it is not a regulated item (Catch-All controls item), the customer service available for that product may be affected. If you have any questions, please consult your local Mitutoyo sales office



Mitutoyo Asia Pacific Pte. Ltd.

Company Reg No. 197800892N

24 Kallang Avenue, Mitutoyo Building, Singapore 339415

Tel: (65) 6294 2211 Fax: (65) 6299 6666

E-mail: mapsg@mitutoyo.com.sg

www.mitutoyo.com.sg | www.mitutoyo.com.my

www.mitutoyo.com.th | www.mitutoyo.co.id

www.mitutoyo.com.vn | www.mitutoyo.com.ph



Mitutoyo (Malaysia) Sdn. Bhd.

Tel: (60) 3-7845 9318

Fax: (60) 3-7845 9346

E-mail: mmsb@mitutoyo.com.my

Penang Branch

Tel: (60) 4-641 1998 Fax: (60) 4-641 2998

Johor Branch

Tel: (60) 7-352 1626 Fax: (60) 7-352 1628

Mitutoyo (Thailand) Co., Ltd.

Tel: (66) 2080 3500

Fax: (66) 2521 6136

E-mail: office@mitutoyo.co.th

Chonburi Branch

Tel: (66) 2080 3563 Fax: (66) 3834 5788

ACC Branch

Tel: (66) 2080 3565

PT. Mitutoyo Indonesia

Tel: (62) 21-2962 8600

Fax: (62) 21-2962 8604

E-mail: ptmi@mitutoyo.co.id

Mitutoyo Vietnam Co., Ltd.

Tel: (84) 24-3768 8963

Fax: (84) 24-3768 8960

E-mail: mvc@mitutoyo.com.vn

Ho Chi Minh City Branch

Tel: (84) 28-3840 3489

Fax: (84) 28-3840 3498

E-mail: mvc@mitutoyo.com.vn

Mitutoyo Philippines, Inc.

Tel: (63) 49-544 0272

Fax: (63) 49-544 0272

E-mail: mpi@mitutoyo.com.ph