

Dial Indicators

Comparison measuring instruments which ensure high quality, high accuracy and reliability.



An inspection certificate is supplied as standard. Refer to page X for details.

SERIES 2 — Standard Type, 0.01mm Graduation

- Standard 0.01mm graduation dial gages having a bezel with an outside diameter of 57mm. All types come with limit markers and a bezel clamp as standard.
- The bezel clamp and lifting lever (optional) can be attached to either the right or left side. These parts can be easily installed and removed without tools.
- Secure adhesion between the bezel and crystal as well as the use of an O-ring prevents water or oil penetration.
- The spindle is made of high-strength quench-hardened stainless steel suitable for heavy-duty use.
- A carbide contact point is used.
- The grand gear is made of stainless steel with high resistance to wear and deformation.
- Application of a hard coating on the surface of the crystal makes the gage highly scratch- and chemical-resistant.



20465



Continuous scale



Graduation: 0.01mm,
Measuring range: 10mm

20465

20465-09

Shockproof type



Balanced scale



Graduation: 0.01mm,
Measuring range: 10mm

20475



Reverse reading type. Suitable for depth and step measurement.



Graduation: 0.01mm,
Measuring range: 10mm

29025



Continuous scale



Graduation: 0.01mm,
Measuring range: 10mm

2310S-10

With coaxial revolution counter

Jeweled bearing type



Continuous scale



Graduation: 0.01mm,
Measuring range: 5mm

20445

20445-09

Shockproof



Balanced scale



Graduation: 0.01mm,
Measuring range: 5mm

20455